

# **IGBT**

## **SGH15N60RUF** Short Circuit Rated IGBT

### **General Description**



Fairchild's Insulated Gate Bipolar Transistor(IGBT) RUF series provides low conduction and switching losses as well as short circuit ruggedness. RUF series is designed for the applications such as motor control, UPS and general inverters where short-circuit ruggedness is required.

### **Features**

- Short Circuit rated 10us @  $T_C = 100^\circ\text{C}$ ,  $V_{GE} = 15\text{V}$
- High Speed Switching
- Low Saturation Voltage :  $V_{CE(\text{sat})} = 2.2 \text{ V}$  @  $I_C = 15\text{A}$
- High Input Impedance
- CO-PAK, IGBT with FRD :  $t_{fr} = 42\text{ns}$  (typ.)

### **Application**

AC & DC Motor controls, General Purpose Inverters, Robotics, Servo Controls



### **Absolute Maximum Ratings**

$T_C = 25^\circ\text{C}$  unless otherwise noted

Symbol	Description	SGH15N60RUF	Units
$V_{CES}$	Collector-Emitter Voltage	600	V
$V_{GES}$	Gate-Emitter Voltage	$\pm 20$	V
$I_C$	Collector Current @ $T_C = 25^\circ\text{C}$	24	A
	Collector Current @ $T_C = 100^\circ\text{C}$	15	A
$I_{CM(1)}$	Pulsed Collector Current	45	A
$I_F$	Diode Continuous Forward Current @ $T_C = 100^\circ\text{C}$	15	A
$I_{FM}$	Diode Maximum Forward Current	160	A
$T_{SC}$	Short Circuit Withstand Time @ $T_C = 100^\circ\text{C}$	10	us
$P_D$	Maximum Power Dissipation @ $T_C = 25^\circ\text{C}$	160	W
	Maximum Power Dissipation @ $T_C = 100^\circ\text{C}$	64	W
$T_J$	Operating Junction Temperature	-55 to +150	$^\circ\text{C}$
$T_{stg}$	Storage Temperature Range	-55 to +150	$^\circ\text{C}$
$T_L$	Maximum Lead Temp. for Soldering Purposes, 1/8" from Case for 5 Seconds	300	$^\circ\text{C}$

Notes :

(1) Repetitive rating : Pulse width limited by max. junction temperature

### **Thermal Characteristics**

Symbol	Parameter	Typ.	Max.	Units
$R_{\theta JC}(\text{IGBT})$	Thermal Resistance, Junction-to-Case	--	0.77	$^\circ\text{C}/\text{W}$
$R_{\theta JC}(\text{DIODE})$	Thermal Resistance, Junction-to-Case	--	0.7	$^\circ\text{C}/\text{W}$
$R_{\theta JA}$	Thermal Resistance, Junction-to-Ambient	--	40	$^\circ\text{C}/\text{W}$

## Electrical Characteristics of IGBT

$T_C = 25^\circ\text{C}$  unless otherwise noted

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
<b>Off Characteristics</b>						
$BV_{CES}$	Collector-Emitter Breakdown Voltage	$V_{GE} = 0\text{V}$ , $I_C = 250\mu\text{A}$	600	--	--	V
$\Delta BV_{CES}/\Delta T_J$	Temperature Coeff. of Breakdown Voltage	$V_{GE} = 0\text{V}$ , $I_C = 1\text{mA}$	--	0.6	--	$\text{V}/^\circ\text{C}$
$I_{CES}$	Collector Cut-Off Current	$V_{CE} = V_{CES}$ , $V_{GE} = 0\text{V}$	--	--	250	$\mu\text{A}$
$I_{GES}$	G-E Leakage Current	$V_{GE} = V_{GES}$ , $V_{CE} = 0\text{V}$	--	--	$\pm 100$	nA

## On Characteristics

$V_{GE(\text{th})}$	G-E Threshold Voltage	$I_C = 15\text{mA}$ , $V_{CE} = V_{GE}$	5.0	6.0	8.5	V
$V_{CE(\text{sat})}$	Collector to Emitter Saturation Voltage	$I_C = 15\text{A}$ , $V_{GE} = 15\text{V}$	--	2.2	2.8	V
		$I_C = 24\text{A}$ , $V_{GE} = 15\text{V}$	--	2.5	--	V

## Dynamic Characteristics

$C_{ies}$	Input Capacitance	$V_{CE} = 30\text{V}$ , $V_{GE} = 0\text{V}$ , $f = 1\text{MHz}$	--	948	--	pF
$C_{oes}$	Output Capacitance		--	101	--	pF
$C_{res}$	Reverse Transfer Capacitance		--	33	--	pF

## Switching Characteristics

$t_{d(on)}$	Turn-On Delay Time	$V_{CC} = 300\text{ V}$ , $I_C = 15\text{A}$ , $R_G = 13\Omega$ , $V_{GE} = 15\text{V}$ , Inductive Load, $T_C = 25^\circ\text{C}$	--	17	--	ns
$t_r$	Rise Time		--	33	--	ns
$t_{d(off)}$	Turn-Off Delay Time		--	44	65	nS
$t_f$	Fall Time		--	118	200	ns
$E_{on}$	Turn-On Switching Loss		--	320	--	uJ
$E_{off}$	Turn-Off Switching Loss		--	356	--	uJ
$E_{ts}$	Total Switching Loss		--	676	950	uJ
$t_{d(on)}$	Turn-On Delay Time		--	20	--	ns
$t_r$	Rise Time		--	34	--	ns
$t_{d(off)}$	Turn-Off Delay Time		--	48	70	ns
$t_f$	Fall Time		--	212	350	ns
$E_{on}$	Turn-On Switching Loss	$V_{CC} = 300\text{ V}$ , $I_C = 15\text{A}$ , $R_G = 13\Omega$ , $V_{GE} = 15\text{V}$ , Inductive Load, $T_C = 125^\circ\text{C}$	--	340	--	uJ
$E_{off}$	Turn-Off Switching Loss		--	695	--	uJ
$E_{ts}$	Total Switching Loss		--	1035	1450	uJ
$T_{sc}$	Short Circuit Withstand Time		$V_{CC} = 300\text{ V}$ , $V_{GE} = 15\text{V}$ $@ T_C = 100^\circ\text{C}$	10	--	us
$Q_g$	Total Gate Charge		--	42	60	nC
$Q_{ge}$	Gate-Emitter Charge	$V_{CE} = 300\text{ V}$ , $I_C = 15\text{A}$ , $V_{GE} = 15\text{V}$	--	7	10	nC
$Q_{gc}$	Gate-Collector Charge		--	17	24	nC
$L_e$	Internal Emitter Inductance	Measured 5mm from PKG	--	14	--	nH

## Electrical Characteristics of DIODE

$T_C = 25^\circ\text{C}$  unless otherwise noted

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
$V_{FM}$	Diode Forward Voltage	$I_F = 15\text{A}$	$T_C = 25^\circ\text{C}$	--	1.4	1.7
			$T_C = 100^\circ\text{C}$	--	1.3	--
$t_{rr}$	Diode Reverse Recovery Time	$I_F = 15\text{A}$ , $dI/dt = 200\text{ A/us}$	$T_C = 25^\circ\text{C}$	--	42	60
			$T_C = 100^\circ\text{C}$	--	60	--
$I_{rr}$	Diode Peak Reverse Recovery Current	$I_F = 15\text{A}$ , $dI/dt = 200\text{ A/us}$	$T_C = 25^\circ\text{C}$	--	3.5	6.0
			$T_C = 100^\circ\text{C}$	--	5.6	--
$Q_{rr}$	Diode Reverse Recovery Charge	$T_C = 25^\circ\text{C}$	--	80	180	nC
			$T_C = 100^\circ\text{C}$	--	220	--




Fig 1. Typical Output Characteristics




Fig 2. Typical Saturation Voltage Characteristics




Fig 3. Saturation Voltage vs. Case Temperature at Variant Current Level






Fig 4. Load Current vs. Frequency

Fig 5. Saturation Voltage vs.  $V_{GE}$ Fig 6. Saturation Voltage vs.  $V_{GE}$




Fig 7. Capacitance Characteristics




Fig 8. Turn-On Characteristics vs. Gate Resistance




Fig 9. Turn-Off Characteristics vs. Gate Resistance




Fig 10. Switching Loss vs. Gate Resistance




Fig 11. Turn-On Characteristics vs. Collector Current













Fig 12. Turn-Off Characteristics vs. Collector Current


**Fig 13. Switching Loss vs. Collector Current**

**Fig 14. Gate Charge Characteristics**

**Fig 15. SOA Characteristics**

**Fig 16. Turn-Off SOA Characteristics**

**Fig 17. Transient Thermal Impedance of IGBT**

**Fig 18. Forward Characteristics****Fig 19. Reverse Recovery Current****Fig 20. Stored Charge****Fig 21. Reverse Recovery Time**

## TRADEMARKS

The following are registered and unregistered trademarks Fairchild Semiconductor owns or is authorized to use and is not intended to be an exhaustive list of all such trademarks.

ACE <sup>x</sup> ™	HiSeC™	SuperSOT™-8
Bottomless™	ISOPLANAR™	SyncFET™
CoolFET™	MICROWIRE™	TinyLogic™
CROSSVOLT™	POP™	UHC™
E <sup>2</sup> CMOS™	PowerTrench®	VCX™
FACT™	QFET™	
FACT Quiet Series™	QS™	
FAST®	Quiet Series™	
FASTR™	SuperSOT™-3	
GTO™	SuperSOT™-6	

## DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

## LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR INTERNATIONAL.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to

result in significant injury to the user.

2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

## PRODUCT STATUS DEFINITIONS

### Definition of Terms

Datasheet Identification	Product Status	Definition
Advance Information	Formative or In Design	This datasheet contains the design specifications for product development. Specifications may change in any manner without notice.
Preliminary	First Production	This datasheet contains preliminary data, and supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
No Identification Needed	Full Production	This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
Obsolete	Not In Production	This datasheet contains specifications on a product that has been discontinued by Fairchild semiconductor. The datasheet is printed for reference information only.